

# Arquivo smb.conf

```
# This is the main Samba configuration file. You should read the
# smb.conf(5) manual page in order to understand the options listed
# here. Samba has a huge number of configurable options (perhaps too
# many!) most of which are not shown in this example
#
# Any line which starts with a ; (semi-colon) or a # (hash)
# is a comment and is ignored. In this example we will use a #
# for commentry and a ; for parts of the config file that you
# may wish to enable
#
# NOTE: Whenever you modify this file you should run the command "testparm"
# to check that you have not made any basic syntactic errors.
#
#===== Global Settings =====
[global]

# workgroup = NT-Domain-Name or Workgroup-Name
    workgroup = MYGROUP

# server string is the equivalent of the NT Description field
    server string = Samba Server

# This option is important for security. It allows you to restrict
# connections to machines which are on your local network. The
# following example restricts access to two C class networks and
# the "loopback" interface. For more examples of the syntax see
# the smb.conf man page
;   hosts allow = 192.168.1. 192.168.2. 127.

# if you want to automatically load your printer list rather
# than setting them up individually then you'll need this
    printcap name = /etc/printcap
    load printers = yes

# It should not be necessary to spell out the print system type unless
# yours is non-standard. Currently supported print systems include:
# bsd, sysv, plp, lprng, aix, hpux, qnx, cups
    printing = cups

# Uncomment this if you want a guest account, you must add this to /etc/passwd
# otherwise the user "nobody" is used
;   guest account = pcguest

# this tells Samba to use a separate log file for each machine
# that connects
    log file = /var/log/samba/%m.log

# Put a capping on the size of the log files (in Kb).
    max log size = 0

# Security mode. Most people will want user level security. See
# security_level.txt for details.
```

```
security = user

# Use password server option only with security = server
# The argument list may include:
#   password server = My_PDC_Name [My_BDC_Name] [My_Next_BDC_Name]
# or to auto-locate the domain controller/s
#   password server = *
;   password server = <NT-Server-Name>

# Password Level allows matching of _n_ characters of the password for
# all combinations of upper and lower case.
;   password level = 8
;   username level = 8

# You may wish to use password encryption. Please read
# ENCRYPTION.txt, Win95.txt and WinNT.txt in the Samba documentation.
# Do not enable this option unless you have read those documents
    encrypt passwords = yes
    smb passwd file = /etc/samba/smbpasswd

# The following is needed to keep smbclient from spouting spurious errors
# when Samba is built with support for SSL.
;   ssl CA certFile = /usr/share/ssl/certs/ca-bundle.crt

# The following are needed to allow password changing from Windows to
# update the Linux system password also.
# NOTE: Use these with 'encrypt passwords' and 'smb passwd file' above.
# NOTE2: You do NOT need these to allow workstations to change only
#         the encrypted SMB passwords. They allow the Unix password
#         to be kept in sync with the SMB password.
    unix password sync = Yes
    passwd program = /usr/bin/passwd %u
    passwd chat = *New*password* %n\n *Retype*new*password* %n\n
*passwd:*all*authentication*tokens*updated*successfully*

# You can use PAM's password change control flag for Samba. If
# enabled, then PAM will be used for password changes when requested
# by an SMB client instead of the program listed in passwd program.
# It should be possible to enable this without changing your passwd
# chat parameter for most setups.

    pam password change = yes

# Unix users can map to different SMB User names
;   username map = /etc/samba/smbusers

# Using the following line enables you to customise your configuration
# on a per machine basis. The %m gets replaced with the netbios name
# of the machine that is connecting
;   include = /etc/samba/smb.conf.%m

# This parameter will control whether or not Samba should obey PAM's
# account and session management directives. The default behavior is
# to use PAM for clear text authentication only and to ignore any
# account or session management. Note that Samba always ignores PAM
# for authentication in the case of encrypt passwords = yes
```

```
obey pam restrictions = yes

# Most people will find that this option gives better performance.
# See speed.txt and the manual pages for details
    socket options = TCP_NODELAY SO_RCVBUF=8192 SO_SNDBUF=8192

# Configure Samba to use multiple interfaces
# If you have multiple network interfaces then you must list them
# here. See the man page for details.
;   interfaces = 192.168.12.2/24 192.168.13.2/24

# Configure remote browse list synchronisation here
# request announcement to, or browse list sync from:
#   a specific host or from / to a whole subnet (see below)
;   remote browse sync = 192.168.3.25 192.168.5.255
# Cause this host to announce itself to local subnets here
;   remote announce = 192.168.1.255 192.168.2.44

# Browser Control Options:
# set local master to no if you don't want Samba to become a master
# browser on your network. Otherwise the normal election rules apply
;   local master = no

# OS Level determines the precedence of this server in master browser
# elections. The default value should be reasonable
;   os level = 33

# Domain Master specifies Samba to be the Domain Master Browser. This
# allows Samba to collate browse lists between subnets. Don't use this
# if you already have a Windows NT domain controller doing this job
;   domain master = yes

# Preferred Master causes Samba to force a local browser election on startup
# and gives it a slightly higher chance of winning the election
;   preferred master = yes

# Enable this if you want Samba to be a domain logon server for
# Windows95 workstations.
;   domain logons = yes

# if you enable domain logons then you may want a per-machine or
# per user logon script
# run a specific logon batch file per workstation (machine)
;   logon script = %m.bat
# run a specific logon batch file per username
;   logon script = %U.bat

# Where to store roving profiles (only for Win95 and WinNT)
#   %L substitutes for this servers netbios name, %U is username
#   You must uncomment the [Profiles] share below
;   logon path = \\%L\Profiles\%U

# Windows Internet Name Serving Support Section:
# WINS Support - Tells the NMBD component of Samba to enable it's WINS Server
;   wins support = yes
```

```
# WINS Server - Tells the NMBD components of Samba to be a WINS Client
# Note: Samba can be either a WINS Server, or a WINS Client, but NOT both
; wins server = w.x.y.z

# WINS Proxy - Tells Samba to answer name resolution queries on
# behalf of a non WINS capable client, for this to work there must be
# at least one WINS Server on the network. The default is NO.
; wins proxy = yes

# DNS Proxy - tells Samba whether or not to try to resolve NetBIOS names
# via DNS nslookups. The built-in default for versions 1.9.17 is yes,
# this has been changed in version 1.9.18 to no.
; dns proxy = no

# Case Preservation can be handy - system default is _no_
# NOTE: These can be set on a per share basis
; preserve case = no
; short preserve case = no
# Default case is normally upper case for all DOS files
; default case = lower
# Be very careful with case sensitivity - it can break things!
; case sensitive = no

#===== Share Definitions =====
[homes]
    comment = Home Directories
    browseable = no
    writable = yes
    valid users = %S
    create mode = 0664
    directory mode = 0775
# If you want users samba doesn't recognize to be mapped to a guest user
; map to guest = bad user

# Un-comment the following and create the netlogon directory for Domain Logons
; [netlogon]
;     comment = Network Logon Service
;     path = /usr/local/samba/lib/netlogon
;     guest ok = yes
;     writable = no
;     share modes = no

# Un-comment the following to provide a specific roving profile share
# the default is to use the user's home directory
; [Profiles]
;     path = /usr/local/samba/profiles
;     browseable = no
;     guest ok = yes

# NOTE: If you have a BSD-style print system there is no need to
# specifically define each individual printer
[printers]
    comment = All Printers
```

```
    path = /var/spool/samba
    browseable = no
# Set public = yes to allow user 'guest account' to print
    guest ok = no
    writable = no
    printable = yes

# This one is useful for people to share files
[tmp]
;    comment = Temporary file space
;    path = /tmp
;    read only = no
;    public = yes

# A publicly accessible directory, but read only, except for people in
# the "staff" group
[public]
;    comment = Public Stuff
;    path = /home/samba
;    public = yes
;    writable = yes
;    printable = no
;    write list = @staff

# Other examples.
#
# A private printer, usable only by fred. Spool data will be placed in fred's
# home directory. Note that fred must have write access to the spool directory,
# wherever it is.
[fredsprn]
;    comment = Fred's Printer
;    valid users = fred
;    path = /home/fred
;    printer = freds_printer
;    public = no
;    writable = no
;    printable = yes

# A private directory, usable only by fred. Note that fred requires write
# access to the directory.
[fredsdire]
;    comment = Fred's Service
;    path = /usr/somewhere/private
;    valid users = fred
;    public = no
;    writable = yes
;    printable = no

# a service which has a different directory for each machine that connects
# this allows you to tailor configurations to incoming machines. You could
# also use the %U option to tailor it by user name.
# The %m gets replaced with the machine name that is connecting.
[pchome]
;    comment = PC Directories
;    path = /usr/local/pc/%m
;    public = no
```

```
; writable = yes

# A publicly accessible directory, read/write to all users. Note that all files
# created in the directory by users will be owned by the default user, so
# any user with access can delete any other user's files. Obviously this
# directory must be writable by the default user. Another user could of course
# be specified, in which case all files would be owned by that user instead.
;[public]
; path = /usr/somewhere/else/public
; public = yes
; only guest = yes
; writable = yes
; printable = no
```

From:

<https://wiki.inf.ufpr.br/maziero/> - **Prof. Carlos Maziero**

Permanent link:

<https://wiki.inf.ufpr.br/maziero/doku.php?id=espec:smb.conf>

Last update: **2008/07/14 23:06**

